quick/install ouide DELPHI

XM Satellite Radio Receiver

Using roadyXT at home*

stereo as illustrated.

Turn off your roadyXT and your home

stereo. Connect your roadyXT to your

Place the antenna on a

*With madeXT Home Kit. (model S&10176, sold senarately)

a stationary home or office environment.

button twice to return to normal operation.

mana disp

To help aim the antenna, use roadvXT's "Antenna Aiming" feature.

Press the "menu" button. Use the arrow and "select" buttons to choose

Find the position that gives at least two bars on either "satellite" or

Terrestr

pre/dr memory jump search

(12) (3 1 4) (5 1 6) (7 1 8) (9 1 9)

DELPH

"Antenna Aiming." This feature is most helpful when using the roadyXT in

Slowly turn and tilt the antenna. The signal bars on the display will change.

The antenna aiming screen remains as long as it's needed to help you posi-

roady?

tion the antenna. When you've found the best position, press the "menu"

Turn on your roadyXT.

"terrestrial."

window or an exterior wall so that it points south.

Mounting roadvXT in your vehicle

your vehicle's interior.

Swivel Mount

or to your vehicle

Find a horizontal air vent that is strong

enough to hold your roadyXT and its

To remove the mount, push it into the

Carefully extract the mount.

vent and lift upwards slightly to release

the mount's hooks from the vent vanes.

plastic tab.

Insert your roadyXT receiver into the vehicle cradle.

Attach the power, antenna, and audio cable (if needed). Tuck the cables under the

Warning: roadyXT should be placed in your vehicle where it will not interfere with the function of safety features

others if the unit becomes detached during an accident and/or obstructs the deployment of an airbag

e.g., deployment of airbags). Failure to correctly place roadyXT may result in death and/or injury to yourself or to

cradle. Clip the vent mount into the vent.

Vent Mount

राजां राजा

We've included two types of mounts to help you install your roadyXT in

Find a suitable location: the mount uses a strong adhesive and you'll have

Peel away the adhesive liner and firmly press

the swivel mount to the surface for 30 seconds. For best results, do not touch or apply any pressure to the vehicle mount for 24 hours.

To remove the mount, lift the adhesive pad

You can adjust the tension of the swivel mount

Base of mount can be rotated to accommodate

vertical or horizontal surfaces. Choose the best

difficulty repositioning it after installation. Do not install this mount on a

with your fingers or a spoon. You may warm it with a hair dryer for 2 to 3

minutes to help soften the adhesive. Remove any leftover adhesive from

by using a screwdriver.

for your installation.

the dash surface by rubbing with your finger, or use a mild cleaner as

Caution: Never use a commercial heat gun or paint-stripping gun. This could result in damage to the unit

leather surface. Make sure the air temperature is at least 60°E.

Clean the mounting surface with the surface preparation

cleaning kit, following the directions on the package.

recommended by your vehicle's manufacturer.

Activating your roadyXT

during peak busy periods.

pushing just one button.

Create a personal stock ticker.

Deep frac

psu/dir mencey jump

(1 2 3 4 5 6 7 8 9 0

· View sports scores, news, and more.

Do more

XM channel

.....

Press the arrow

buttons to find

channel 0. Push

You'll see an 8-

ID in the display.

(The XM Badio ID

does not use the

to choose it.

the "select" button

character XM Badio

letters I. O. S. and E.)

1 40

roady×t

XM will send a signal from the satellites to activate the full channel lineup.

When you can access the full channel lineup on your roadyXT, you're done!

Activation normally takes 10 to 15 minutes, but may take up to an hour

· Save favorite channels as presets, which you can instantly recall by

Use TuneSelect^{**} to find your favorite songs when they play on any

ABC

Rowie

Save and recall the artist names and titles of your favorite songs.

Check out your roadyXT User Guide for more information.

paulder message jump search

(12) (314) (514) (714) (914)

You will need the XM Badio ID and a major credit card.

Activate your XM Satellite Badio service by contacting XM at http://activate.xmradio.com or by calling 1.800.XM.RADIO (1.800.967.2346).





SA10176 SA10178

SA10175



Important: This manual contains important safety and operating information. Please read, understand, and follow the instructions in this manual. Failure to do so could result in personal injury, death, and/or damage to your roady XT. accessories, and/or to your vehicle or property.

injury hazards. Obey all safety messages that follow this symbol to avoid

This is the safety alert symbol. It is used to alert you to potential personal

Receiver for use in any aircraft (neither portable nor permanent installation). Therefore,

The Delphi XM^e roadyXT Satellite Radio Receiver incorporates an FM transmitter and is

expressive approved by meiphi can void your authority to operate this equipment. therefore classified as an intentional transmitter. Changes or modifications to the unit not

Marning: The FCC and FAA have not certified the Delphi XM roadyXT Satellite Radio

150-350-553 Tata metar noticutory ya utuar serenegy The projection in particular

roacy, ri, the XM name, Lumowerd, and reason logos are trademarks of XM Satellite Radio Inc.

moo.idqlab.www

Irak, Michigan 48098-5090

DELPHI



FCC ID: RS2SA101777

bossiple injury or dearn.

Delphi cannot support this type of application or installation.

including interference that may cause undesired operation. 2. This device must accept any interference received,


7. This device may not cause harmful interference, and Operation is subject to the following two conditions:

This device complies with Part 15 of the FCC Rules.









Remote Control*

up and down arrows, selec change channels, choose menu options, TuneSelect

search - look up

channels by category

pre/dir - select between

direct channel entry or -up to 30 presets

disp - change what you

channel number, stock quotes, or Info Extras

*Sold separately

see on the display; show artist name, song title

or scan all channels


Using roadvXT in your vehicle

Because every vehicle is different, we can only provide some general guidelines. If you need help, consult a professional installer.

- · Decide which method (cassette adaptor, wired connection, or wireless FM transmitter) is best for your vehicle and location.
- Always do a trial run before installing anything permanently. Temporarily connect all power, audio, and antenna lines. Make sure that you receive the XM signal and that you hear XM programming through your vehicle's audio system.


Audio quality





way to hear XM programming in your vehicle. Simply set your FM radio and your roadyXT to

Display



Ticker, and Info Extras

Remember to pull out the clear plastic tab from the remote battery compartment before using the remote.

 \supset

0 A

50

ÓÓĆ

244

-5-0 Z

DELPH

ē

문

To remove the battery from the remote, use your thumb to press the center of the battery tray and pull it out. Replace the battery with the equivalent size and voltage, taking care to insert it with the positive (+) side up.

menu - access

advanced features and configuration options

 and – change channels or control volume if roadyXT is placed in a Delphi audio system

jump - return to previous channel; press and hold to select one of last six

FM frequencies used for

numbers - enter a channel directly or

memory - save and

recall up to 20 artist names or song titles

modulator



Placing the antenna For best reception, place the XM antenna on the vehicle's metallic roof, at least

6" from any window or sunroof. It can be placed in the front, middle, or rear of the roof.

If the car is a hard- or soft-top convertible, you may mount the antenna on the metal trunk lid. It should be at least 4" from the rear window. Ensure that the antenna and cable don't interfere with the opening or closing of the convertible top and the trunk lid.

TIP: If you route the antenna cable through the trunk seal, use the lowest part of the weather seal. This should minimize any water leaks.

TIP: If you use your roadyXT's wireless FM transmitter, mount the XM antenna as close to your vehicle's FM antenna as possible. The FM antenna may be a wire or metallic strip embedded in the windshield or rear window.

TIP: Don't install the XM antenna inside your vehicle or on a non-metallic surface. Doing so will likely degrade the signal and you will probably experience more signal interruptions.

